

## Bonding Block 84

Primer for interior plaster work



<b>Description</b>	Primer for interior plaster work	
<b>Features</b>	Solvent-free and plasticizer-free, absorbency-regulating	
<b>Application</b>	Primer for the consolidation of the upper layers of sanding and porous plasters and for the reduction and levelling of the absorption behaviour. All substrates must be dry, load-bearing, clean and free of adhesion-reducing residues.	
<b>Consumption</b>	Approx. 0.1-0.15 l/m <sup>2</sup>	
<b>Technical data</b>	Type	Yellowish Primer
	Consistency	Liquid
	pH value	11
	Density	approx. 1.0 kg/dm <sup>3</sup>
<b>Processing</b>	<p>Stir thoroughly with a slow-running agitator and dilute to 1 : 3 with water. Sanding and highly absorbent substrates must be solidified with Deep Primer LF. Apply with a roller or brush.</p> <p>Clean tools immediately after use with water. Carefully cover adjacent surfaces. Wash off splashes immediately with plenty of water. Do not use at air and building temperatures below +5°C as well as in direct sunlight, draughts or expected night frosts. Immediately clean surfaces contaminated with paint splashes thoroughly with water!</p> <p><b>Keep out of the reach of children.</b>          In case of contact with eyes and skin, rinse immediately with water.          Do not inhale spray mist during spray application!  <b>Do not allow to reach water bodies or sewers.</b></p>	
<b>Surface coating</b>	Depending on the application, the primed surfaces can be treated with all adhesive and reinforcing mortars, silicone resin or dispersion products after sufficient drying (at least 24 hours at 20°C).	
<b>Form of Delivery</b>	10.0 l/container (40 containers/pallet)	
<b>Storage</b>	Keep canisters tightly closed, cool and frost-free.	
<b>Reference</b>	Protect eyes and skin. Giscode: M-GF01	
<b>Consulting service</b>	The information given in this data sheet is only general guidelines. Should technical questions arise in a specific application, please contact our sales office.	
<b>Optics</b>	-	
<b>Colour</b>	Opaque	
<b>Options</b>	-	

## **Bonding Block 84**

Primer for interior plaster work

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual Data and statements are excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction engineering as well as the applicable standards and guidelines must be observed. Previous editions are invalid with the publication of this publication. We reserve the right to make changes within the scope of further product and application developments. Please refer to our Internet pages for the latest information. For all business transactions, our current Terms and conditions of sale and delivery.

### **HUMA FARBEN GmbH**

Ziegelfeldstraße 66 D-73563 Mögglingen

Fon +49.(0)7174.89899-0

Fax +49.(0)7174.89899-18

[www.huma-farben.de](http://www.huma-farben.de) [info@huma-farben.de](mailto:info@huma-farben.de)