

## Crack Filler

For filling cracks



<b>Description</b>	For filling cracks	
<b>Features</b>	Low shrinkage, crack-free drying, fiber-reinforced	
<b>Application</b>	Outside and inside	
<b>Consumption</b>	Depending on substrate	
<b>Technical data</b>	Density	approx. 1.8 kg/m <sup>2</sup>
	Adhesion	>= 0,3 MPas according to EN 1542
<b>Processing</b>	<p>Sanding and highly absorbent substrates are to be strengthened with Deep Primer LF. Application with a brush or brush. Basically expand cracks as V-joints. Fill in cracks in 1-2 working steps and level out.</p> <p>Clean tools immediately after use with water. Carefully cover adjacent surfaces. Wash off splashes immediately with plenty of water. Do not use at air and building temperatures below +5°C as well as in direct sunlight, draughts or expected night frosts.</p> <p>Immediately clean surfaces contaminated with paint splashes thoroughly with water!</p> <p><b>Keep out of the reach of children!</b> In case of contact with eyes and skin, rinse immediately with water.. <b>Do not allow to reach water bodies or sewers!</b></p>	
<b>Surface coating</b>	After sufficient drying (min. 24 hours at 20°C) coating with mineral or pasty products.	
<b>Form of Delivery</b>	5.0 kg/bucket (64 buckets/pallet)	
<b>Storage</b>	Store buckets tightly closed, cool and frost-free.	
<b>Reference</b>	Protect eyes and skin. Giscode: M-DF02	
<b>Consulting service</b>	The information given in this data sheet is only general guidelines. Should technical questions arise in a specific application, please contact our sales office.	
<b>Optics</b>	Fine roughness	
<b>Colour</b>	White	
<b>Options</b>	-	

All information in this publication is based on experience, tests and trials. A guarantee for the general validity of individual Data and statements are excluded with regard to different processing and construction site conditions. The generally recognised and technical rules of construction engineering as well as the applicable standards and guidelines must be observed. Previous editions are invalid with the publication of this publication. We reserve the right to make changes within the scope of further product and application developments. Please refer to our Internet pages for the latest information. For all business transactions, our current Terms and conditions of sale and delivery.

## Crack Filler

For filling cracks

### **HUMA FARBEN GmbH**

Ziegelfeldstraße 66 D-73563 Mögglingen

Fon +49.(0)7174.89899-0

Fax +49.(0)7174.89899-18

[www.huma-farben.de](http://www.huma-farben.de) [info@huma-farben.de](mailto:info@huma-farben.de)